

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

1 Identification

- **Product identifier**
- **Trade name:** **(±)8(9)-DiHET MaxSpec® Standard**
- **Synonym** (±)8,9-dihydroxy-5Z,11Z,14Z-eicosatrienoic acid; (±)8,9-DiHETrE
- **Article number:** 10007265, 007858
- **Application of the substance / the mixture**
This product is for research use - Not for human or veterinary diagnostic or therapeutic use. It is the responsibility of the purchaser to determine suitability for other applications.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cayman Chemical Co.
1180 E. Ellsworth Rd.
Ann Arbor, MI 48108
USA
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (734) 971-3335
US/CANADA: 800-424-9300
Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapor.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 0
 Fire = 3
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
 Fire = 3
 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64-17-5	Ethyl alcohol	99.999%
RTECS: KQ6300000		

- **Other ingredients**

192461-96-4	(±)8(9)-DiHET	0.001%
-------------	---------------	--------

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
Can release vapors that form explosive mixtures at temperatures at or above the flashpoint.
Container explosion may occur under fire conditions.
Emits toxic fumes under fire conditions.
Sensitive to static discharge.
Vapors can travel to a source of ignition and flash back.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

64-17-5	Ethyl alcohol	1,800 ppm
---------	---------------	-----------

- **PAC-2:**

64-17-5	Ethyl alcohol	3300* ppm
---------	---------------	-----------

- **PAC-3:**

64-17-5	Ethyl alcohol	15000* ppm
---------	---------------	------------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Store upright and unopened at -20C.
Warm to room temperature before opening.
Light sensitive.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Avoid prolonged or repeated exposure.
Keep away from sources of ignition.
Take precautionary measures against static discharge.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 3)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

64-17-5 Ethyl alcohol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

According to product specification

· Odor:

Characteristic

· Structural Formula

C₂₀H₃₄O₄

· Molecular Weight

338.5

· Odor threshold:

Not determined.

· Formulation

A solution in ethanol at 10 µg/ml

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

-114.5 °C (-174.1 °F)

Boiling point/Boiling range:

78 °C (172.4 °F)

· Flash point:

13 °C (55.4 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

425 °C (797 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:

3.5 Vol %

Upper:

15 Vol %

· Vapor pressure at 20 °C (68 °F):

59 hPa (44.3 mm Hg)

· Density at 20 °C (68 °F):

0.79 g/cm³ (6.59255 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

Water at 20 °C (68 °F):

1,000 g/l

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F):

1.2 mPas

Kinematic:

Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 5)

· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	1,000.0 g/l / 8.35 lb/gal
· Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64-17-5 Ethyl alcohol

Oral	TDLO	1.14 ml/kg (man)
	LD50	7,060 mg/kg (rat)
Dermal	TDLO	650 (man)
	LD50	40,000 mg/kg (rat)
	Inhalative	LC50/4 h
		5,900 mg/m ³ (rat)
	LC50	20,000 mg/m ³ /10h (rat)
	TCLO	1,800 mg/m ³ /30m (hmn)
	LCLO	29,300 mg/m ³ /7h (mouse)
	TCLO	1,800 (hmn)
	LC50	10 h - 20,000 mg/m ³ (rat)
	LD50 Inhalation TCLO	1,800 mg/m ³ /30m (hmn)
Irritation of skin	LC50/4 h	20,000 mg/l (rat)
	Irritation	20 mg/24h (rabbit)
Irritation of eyes	TDLO	1,800 mg/kg (wmn)
	Irritation	500 mg/24h (rabbit)
	Intraperitoneal LD50	280 mg/kg (rat)
	Data	500 mg/24h (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 6)

- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

64-17-5 Ethyl alcohol

1

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA**

UN1170

- **UN proper shipping name**

- **DOT**

- **IMDG**

- **IATA**

Ethanol solutions

ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Ethanol solution

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 7)

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, IMDG, IATA

II

· Environmental hazards:

Not applicable.

· Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

· EMS Number:

F-E,S-D

· Stowage Category

A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· IATA

· Remarks:

When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.

· UN "Model Regulation":

UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 8)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

64-17-5 Ethyl alcohol

ACTIVE

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

64-17-5 Ethyl alcohol

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

64-17-5 Ethyl alcohol

A3

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

- **Department issuing SDS:** Environment protection department.

- **Contact:** -

- **Date of preparation / last revision** 04/26/2021 / -

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/26/2021

Revision date 04/26/2021

Trade name: (±)8(9)-DiHET MaxSpec® Standard

(Contd. from page 9)

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2

— US —